

10106245 TKE/P 40+/RD LG

Tails Kit Plastic M32/M40 with multiple sealing insert



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Material cable gland	Polyamide
Material sealing gasket	EPDM
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP66, IP68 (5 bar 30 min)
Product Color	RAL 7035
Thread type	M
Ø Connection thread D	40
Lead	1,5
Length screw-in thread L	12 mm
Key width SW	46 mm
Total length TL	53 mm - 62 mm
Glow wire test	750 °C
Type of cable anchorage	A
Install. torques fitting	10 N/m
Install. torques cap nut	4 N/m
Impact category	4
Order no. RAL 7035	10111752
Type	10106245 TKE/P 40+/RD LG
Packing unit	1
ETIM-Classification	EC000441

Description:

UNIVERSAL OPTION Suitable for 32 or 40 mm. IP68 Plastic cable gland. ESKV 40+/ MFD 2 x 11mm Tails and 1 x 6mm Earth, 1 KEM Adaptor 40 - 32mm. Kit contains multiple sealing insert, locknut, blanking insert and KEM reduce.

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

25.11.2023

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk