

APRILED/CW



Features

IP65 LED dimmable fire-rated performance downlight for domestic applications

Supplied with matt white bezel as standard.

Integral driver with push-fit loop-in, loop-out terminals for ease and speed of installation.

Fully tested for 30, 60 and 90 minute ceiling types to meet Part B of Building Regulations.

Fully tested to meet Part C (moisture) and Part E (acoustic) of Building Regulations.

Wide 60° beam angle for increased light distribution.

LED lifespan L70 60,000 hours.

General Information

| | |
|--------------------------------|--|
| Lamp Type | LED |
| Colour / Finish | Matt White |
| Fire Rated | Yes |
| OCTO Compatibility | Smart Indoor controller |
| IP Rating | IP65 |
| Class Protection | 1 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Diameter (mm) | 95 |
| Height (mm) | 102 |
| Accessories | APRILEDZ/CH, APRILEDZ/SC, AORBLED/DIMMER |


Technical Information

| | |
|------------------|--------------|
| Wattage | 7W |
| Lumens Delivered | 715lm |
| Lm/W | 102lm |
| Beam Angle | 60 |
| CRI | Ra 80 |
| CCT | 4000K |
| Input | 230V |
| Hertz | 50Hz |
| Operating Temp | -5°C to 25°C |

Technical Data - ETIM - Downlight/spot/floodlight (EC001744)

| | |
|--|------------------|
| Suitable for surface mounting | No |
| Suitable for built-in mounting | Yes |
| Suitable for wall mounting | No |
| Suitable for suspended mounting | No |
| Suitable for ceiling mounting | Yes |
| Suitable for traverse mounting | No |
| Suitable for pedestal/floor mounting | No |
| Suitable for light-track mounting | No |
| Adjustability | Not adjustable |
| With movement sensor | No |
| With light sensor | No |
| With light source | Yes |
| Suitable for number of lamps | 1 |
| Colour housing | White |
| Nominal voltage | 230-230 V |
| Control gear included | Yes |
| Light distributor | Reflector |
| Beam angle | Wide beam 41-80° |
| Degree of protection (IP) | IP65 |
| Protection class | I |
| Max. system power | 7 W |
| Colour of light | White |
| Colour temperature | 4000-4000 K |
| Colour rendering index CRI | 80-89 |
| Rated luminous flux acc. IEC 62722-2-1 | 715 lm |

| | |
|----------------|----------|
| Lamp efficacy | 102 lm/W |
| Height/depth | 102 mm |
| Length | 87 mm |
| Outer diameter | 95 mm |



Datasheet generated from <https://onetimepim.com> last updated Monday, September 6, 2021 12:47:50 PM