


Technical Specification

Luckinslive 393319796


Description: 45A Ingot 2 Gang Double Pole Switch With 13A Double Pole Switched Socket

Outlet

Product Code: VPBN504BK







General Information

Plate Dimensions (mm) $146 \text{ (W)} \times 88 \text{ (H)} \times 8 \text{ (D)}$

Dimensions With Gasket (mm) $149 \text{ (W)} \times 91 \text{ (H)} \times 9 \text{ (D)}$

Plate Fixing Centres - Horizontal (mm) 120.6

Style Victorian

Finish Black Nickel

Insert Colour Black
Gasket Colour Black

Materials Front Plate: Stainless Steel

Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Anti Microbial Certified No

Operating Voltage (AC) 250

Resistive Load Rating (A) 45

Termination Type Screw

Terminal Size (mm) Ø6

Terminal Capacity - Solid (mm²) 1 x 16

Double Pole Switch Yes

Twin Earth Terminals Yes

Product Marking Cooker

Minimum Back Box Depth (mm) 35

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS 4177

Insert & Rear Housing: Urea

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Frequency (Hz) 50

Terminal Torque Value (Nm) 2.5

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal













Specification is subject to change without notice. Errors & Omissions excluded.