

Product Code: VPBN551BK

Technical Specification

Luckinslive 390053055

Description: 13A Ingot Double Pole Switched Fused Connection Unit With Optional Flex Outlet







Earth Strap: Mild Steel

General Information

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

Style Victorian

Finish Black Nickel

Insert Colour Black Gasket Colour Black

> Materials Front Plate: Stainless Steel Insert & Housing: Urea Terminals: Brass

Switch & Fuse Drawer Cover: Stainless Steel

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Anti Microbial Certified

Frequency (Hz) 50 Operating Voltage (AC) 250

Resistive Load Rating (A)

Fuse Fitted Type Plug Top Cartridge Fuse

Termination Type Screw

Terminal Size (mm) Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

> Switched Yes

Double Pole Switch Twin Earth Terminals Product Marking Fused Flex Outlet Available Yes

Flex Outlet Location Front of Plate Flex Outlet Dimension (mm) Ø10

Minimum Back Box Depth (mm) 25

Ingress Protection IP20 Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom

Specification is subject to change without notice. Errors & Omissions excluded.









