Aventa In-Line

Light commercial ventilation







Key Features

- In-Line mixed flow fan
- Flow rate up to 520 m³/hr
- Designed for ducted installations
- High pressure, low noise
- Compact and quiet in operation
- Two speed (normal and boost)
- Adjustable overrun timer version
- Access to monitor and impeller without dismantling ductwork
- Low watt motor 30w
- IPX4 rating
- Complies with Building Regulations
- 3 year warranty

Aventa In-Line range

The Aventa range provides compact, quiet and powerful remote mounted ventilation for ducted installations. Available in high performance, two speed versions they are less bulky than larger in-line centrifugal fans and can be installed in loft spaces or service shafts for remote extraction.

With high flow/high pressure development characteristics they can be used with flexible ducting and flat duct

systems to ensure compliance with Building Regulations guidance ensuring installed performance and extraction conditions are met.

Combining two Aventa fans allows for even more powerful operation. Mounting in parallel (left hand image on facing page) doubles the air flow, whilst two fans in series (right hand image on facing page) leads to a doubling of the air pressure for longer duct runs.







Models

Basic Pasic remote switching


Timer can be set to run on between 2 and 30 minutes



Technical Data


Specification	Aventa 150B Aventa 150T		
Air flow m³/hr	405 / 520	405 / 520	
Air flow I/sec	112 / 144	112 / 144	
Fan type	Mixed Flow Mixed Flow		
Controls	Basic Timer		
Mounting	In-Line	In-Line	
Sound Pressure dB(A)@3m	33 / 44	33 / 44	
Power watts	30 / 60	30 / 60	
Amps	0.17 / 0.27	0.17 / 0.27	
Building Regulations ADF	Yes	Yes	
Duct diameter (mm)	150	150	
Voltage	230v / 1ph / 50Hz	230v / 1ph / 50Hz	
Rating	IPX4	IPX4	
Material finish	ABS	ABS	
Weight (kg)	3.4	3.4	
Dimensions (H x W x D) mm	250 x 295 x 185 251 x 295 x 185		
Part No.	9041089	9041090	

Dimensions (mm)



Model	Α	В	С	D	E
AV150	148	295	250	250	185

Performance





Double the flow - mount in parallel



Double the pressure - mount in series

Controls and Accessories

A range of accessories including flexible and rigid ducting kits, controls and grilles are available.

See accessories section from page 205 for more details.