



## ATSLED/3NM/ST/HO



### Features

Self-test Twin LED emergency floodlight for industrial applications

Exceeds performance of 2x20W halogen equivalent

Robust white moulded enclosure

Moulded polycarbonate heads

Self-test as standard

## General Information

Lamp Type	LED
Colour / Finish	White
Self Test	Yes
IP Rating	IP66
Class Protection	1
Internal / External	Internal/External
Surface / Recessed / Suspended	Surface
Warranty (Years)	5
CE Mark	Yes
Width (mm)	300
Height (mm)	290
Depth (mm)	70
Accessories	ASBP/6/LI

## Technical Information

Wattage	3.3W
Lumens Delivered	670lm (Emergency)
CCT	6500K
Input	220V-240V
Hertz	50Hz
Operating Temp	5C° to 40C°

## Technical Data - ETIM - Emergency luminaire (EC001957)

<b>Mounting method</b>	Wall surface mounted
<b>Monitoring equipment</b>	Automatic self test
<b>With light source</b>	Yes
<b>Number of lighting heads</b>	2
<b>Material housing</b>	Plastic
<b>Colour housing</b>	White
<b>Nominal voltage</b>	220-240 V
<b>Degree of protection (IP)</b>	IP66
<b>Protection class</b>	I
<b>Max. system power</b>	3.3 W
<b>Colour temperature</b>	6500-6500 K
<b>Width</b>	300 mm
<b>Height/depth</b>	70 mm
<b>Length</b>	290 mm

Datasheet generated from <https://onetimepim.com> last updated Friday, February 18, 2022 4:21:35 PM

