

AWO50



Features

Supplied with both MR16 and GU10 lampholders.

Compact inground uplight which accepts 12V and mains halogen, CFL and LED lamps.

Housing in die-cast aluminium with clear toughened glass diffuser of 10mm thickness.

316 stainless steel top ring and stainless steel allen key screws.

Suitable for light vehicular traffic with a static impact resistance of up to 2000kgs.

Supplied with recessed sleeve in high resistant thermoplastic.

General Information

Lamp Type	MR16 / GU10
Colour / Finish	Stainless Steel
OCTO Compatibility	Smart Outdoor controller
IP Rating	IP67
Class Protection	1, 3
Internal / External	External
Surface / Recessed / Suspended	Recessed
Warranty (Years)	3
CE Mark	Yes
Diameter (mm)	98
Depth (mm)	155

Technical Information

Wattage	50W
---------	-----

Technical Data - ETIM - In-ground luminaire (EC000758)

Lamp type	Other
-----------	-------

With light source	No
-------------------	----

Suitable for number of lamps	1
------------------------------	---

Colour housing	Stainless steel
----------------	-----------------

Material cover	Glass transparent
----------------	-------------------

Degree of protection (IP)	IP67
---------------------------	------

Max. system power	50 W
-------------------	------

Height/depth	155 mm
--------------	--------

Outer diameter	98 mm
----------------	-------

Max. load	2000 kg
-----------	---------

Over rollable	Yes
---------------	-----

Datasheet generated from <https://onetimepim.com> last updated Friday, February 18, 2022 12:23:45 PM

