

Commercial Fan Heaters - Wireless Controlled

Our commercial fan heaters provide a "heat throw" of 11m at maximum fan speed. The intelligent fan control optimises fan speed and heat output to quickly achieve and control a comfort temperature whilst maintaining a very low noise level. Provides comfort heating while working in garages, workshops and warehouses.

- 6kW, 9kW & 12kW ratings.
- Requires a separately purchased CHMC, HRXSL or CRXSL wireless controller.
- Single phase or 3 phase models.
- Sensor to detect the room temperature.
- Intelligent Fan Control feature:- The fan speed of the heater automatically adjusts relative to the room's current temperature in order to achieve warm airflow temperature. This eliminates the heater from blowing cold air when initially powered on in a cold room.
- Incorporates EC motor for improved energy efficiency.
- Electronic fault monitoring.
- One CRXSL controller can operate multiple heaters in single zone configuration.
- One CHMC controller can operate a maximum of 8 heaters with individual control.
- Time/Manual mode in CRXSL controller:
 - Allows fan and heat settings to be adjusted manually.
 - Allows set time schedule for fan and heat settings.
- CRXSL controller is compatible with separately purchased MRX1 Multizone controller for 'zoning' of the heating system.
- Option to select room temperature measurement on HRXSL or heaters.
- Instant directional warmth.
- 3 fan speeds, 3 heat settings with CRXSL (in Manual mode).



- 8 fan speeds, 8 heat settings with CHMC (in Manual Mode).
- Fan only setting for air circulation.
- Wall mounted with multi-directional brackets supplied (180° horizontal, 45° vertical).
- Maximum heat throw – 11 metres.
- Finished in white/grey.

Commercial Heater Environmental Sensor (CHES) - Optional indoor sensor

- Compatible with CHMC controller
- Occupancy sensor
- Temperature sensor
- Remote switch connection for On/Off function or Boost



Model No.	Optimum Mounting Height (m)	Single Phase	3 Phase
CH06CSiRX	2 - 3.4	●	
CH06CPiRX	2 - 3.4		●
CH09iRX	2 - 3.4		●
CH12iRX	2 - 3.4		●

Dimensions (mm) & Weight (kg):

Height	Depth	Width	Weight	Max. dBA
272	338	332	11.5	59

CRXSL & HRXSL Energy Saving Features

- 6 temperature programmes per day
- 7-day heating programmes per week
- Maintains temperature within 0.5°C
- Set temperature in 0.5°C increments

CHMC Quick Feature Guide

- Can control up to 8 heaters as a group or individually
- Temperature sensor
- 8 fan speeds and 8 heat settings in Manual mode
- 7-day timer with 2 heating periods per day
- Wi-Fi enabled for connection to Consort Connect app - App provides full functionality of CHMC remotely