

Technical Specification

ESP. Scolmore GROUP

Access Control Accessories

Product Code: EVBPSBB Description: Boxed Power Supply



General Information		Supply & Power	
Dimensions (m	n) 129 x 73 x 50	Supply Voltage (V AC)	100 - 230
	ABS ABS Surface	Input Type	Coil (to activate lock output switch over)
Warranty (Year	0	Activation Type	Energise with a Normally Open Clean contact
Ingress Protection		Output Type	Configurable Normally Open or Normally Closed
Operating Temperature (°C)	0 to +50	Number of Outputs	2 (1 x Switched & 1 x Constant)
		Constant Output	12V @ 1A
		Lock output	12V DC @ 1.5A

Supplied Fixing Screws, and Wall Plugs, User Manual, Battery Cables

Accessories
,

Optional Battery Backup
Suitable for both Fail-Safe & Fail-Secure locks
Can be provided from a better unen major failure, and a

Can be powered from a battery upon mains failure, and charge SLA 12V Batteries.

BAT32: 12V 3.2Ah SLA Battery
BAT7: 12V 7Ah SLA Battery
BAT18: 12V 17Ah SLA Battery
EV-EXIT: Push to Exit Release Button
EV-EBG: Green Emergency Break Glass
ENTERD: Flush Electronic Lock
ENTERD-YLR: Surface Electronic Lock
EV-ML-250: Electromagnetic Lock
EV-ML-500XT: External Electromagnetic Lock

Additional Information Upon Power Failure, if a battery is connected it will power the unit.

