

**Product Code:** EZT3K

**Description:** Single Internal Door Proximity Keypad Kit c/w Flush Exit Button



### Supplied

- 1 x EZTAG3
- 1 x EVBPSBB
- 1 x A1EXIT
- 1 x A1ECP
- 1 x A1ML250

### Component 1

EZTAG3 - Proximity & Keypad Door Entry

### Quantity

1

### Component 2

EVBPSBB - Power Supply Unit with Battery Backup

### Quantity

1

#### General Information

Dimensions (mm)	150 x 44 x 24
Finish	Silver
Materials	Aluminium
Mounting	Surface
Fob Reader Operating Frequency (KHz)	125
Fob Reader Operating Distance (mm)	<50
PIN length	2 - 6 Digits
Maximum Capacity	Zone 1; 1000 Fob/PIN Zone 2; 10 Fob/PIN
Backlight	Keys; Blue LEDs
Tamper Facility	Yes
Status Indication	Red, Green, and Amber LEDs

#### Supply & Power

Operating Voltage (V DC)	12 - 24
Operating Current (mA)	110
Unlatched Relay Time	1 - 99 Seconds
Maximum Switchable Load	30V @ 4A
Operation Type	Latched & Unlatched
Lock outputs	2

#### Inputs & Outputs

Relay Types	Normally Open & Normally Closed; Volt-Free
-------------	--

#### Environment

Ingress Protection	IP65
--------------------	------

#### General Information

Dimensions (mm)	129 x 73 x 50
Materials	ABS
Mounting	Surface Only
Supply Voltage (V AC)	100 - 230
Output Type	Configurable Normally Open or Normally Closed
Number of Outputs	Configurable Normally Open or Normally Closed2 (1 xSwitched & 1 xConstant)
Lock output	12V DC @ 1.5A
Ingress Protection	IP20
Operating Temperature (°C)	0 to +50

### Component 3

A1EXIT - Flush Push to Exit Release Button

### Quantity

1

### Component 4

A1ECP - Green Internal Emergency Call Point

### Quantity

1

#### General Information

Dimensions (mm)	86 x 86 x 22
Finish	Brushed Steel
Materials	Stainless Steel
Mounting	Surface or Flush (Backbox not Included)
Relay Voltage	125-250V
Contact Type	2 x SPST (Normally Open & Normally Closed)
Output Relay Rating	3A @125-250V AC
Operating Temperature (°C)	-20 to +55

#### General Information

Dimensions (mm)	87.5 x 87.5 x 32
Finish	Green (RAL6016)
Materials	Fire Resistant ABS
Mounting	Surface or Flush (Backbox Included)
Contact Type	Double Pole Double Throw
Output Relay Rating	3A @125-250V AC
Operating Temperature (°C)	-20 to +55
Weight (Kg)	0.17





**Component 5**

**Quantity**

A1ML250 - Internal 250kg Holding Force Magnetic Lock with Z and L Brackets

1

**General Information**

Dimensions (mm)	48 x 250 x 27
Finish	Brushed Silver
Materials	Aluminium Alloy
Mounting	Surface Only
Maximum Holding Force (Kg)	250
Operating Voltage (V DC)	12 & 24
Operating Temperature (°C)	-20 to +50