



**5**  
Year Warranty



IP65



IK08



Photocell





✓ IES Files



Earthed



Hole Knockouts



Photocell



20mm knockouts



Captive stainless steel screws



**Eterna**  
Everyday Lighting For Professionals

**30W INTEGRATED LED BULKHEAD**

Robustly constructed & suitable for multiple commercial use where performance and functionality are required

- Captive stainless steel screws
- Tough polycarbonate housing
- 20mm knockouts side and rear

**PHOTOCELL VERSION:** photocell for dusk to dawn operation

Code	Version	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP / IK Rating	MOM / OPQ
WPACKLED	Standard	30W	4200K	2000 lm	30,000 hrs	IP65 IK08	1 / 4
WPACKLEDPC	Photocell						

**LED LAMP SPECIFICATIONS:**

Lumens total flux	<b>2000 lm</b>
Rated Wattage	30W
Rated luminous flux	2000 lm
Nominal life time of the lamp	30,000 hrs
Colour temperature	4200K
Number of switching cycles before premature lamp failure	≥15,000
Warm-up time up to 60 % of the full light output	Instant full light
Dimmable	No
LED array dimensions (W/H)	198 x 167mm
Nominal beam angle	120°
Rated power	30W
Rated lamp lifetime	30,000 hrs
Displacement factor	
Lumen maintenance factor at end of nominal life	≥0.70
Starting time	<0.1s
Colour rendering	≥80
Colour consistency	Within 6 step Macadam ellipse
Rated peak intensity	720cd
Rated beam angle	120°
Voltage	220/240V

This product contains a Light Source of Energy Efficiency Class G

Not suitable for accent lighting